

# striesuede

## Specifications

<b>Contents:</b>	47% Recycled Polyester, 41% Polyester, 12% Polyurethane
<b>Width:</b>	56"
<b>Weight:</b>	13.9 oz. per Linear Yard / 265 Grams per Square Meter
<b>Thickness:</b>	0.80mm
<b>Durability:</b> Wyzenbeek: Martindale:	75,000 Double Rubs Heavy Duty Contract
<b>Fabric Strength:</b> ASTM D-5034	Exceeds Industry Standards
<b>Piling Resistance:</b> ASTM D-3511	Exceeds Industry Standards
<b>Seam Strength:</b> ASTM D-4034	Exceeds Industry Standards
<b>Colorfastness:</b> Color Rub-Off (AATCC-8 Crocking) To Light (AATCC-16E)	Exceeds Industry Standards Exceeds Industry Standards
<b>Fire Test Compliance:</b> UFAC Cig. Smoldering Test NFPA-260 CA TB-117 Sec. E ASTM E-84 Tunnel Test (Adhered & Unadhered)	Complies with Industry Standards Complies with Industry Standards Complies with Industry Standards Complies with Industry Standards
<b>Maintenance &amp; Care</b>	Water or solvent based cleaning agent machine washable or dry-cleanable

**Striesuede** contains high-purity recycled polyester from post-consumer and post-industrial sources.

The advanced recycling process uses significantly less energy, eliminates the use of toxic organic solvents, and emits less carbon dioxide than the manufacture of virgin polyester.

**Striesuede** is manufactured in an ISO 14001 / ISO 9001:2000 certified facility and complies with Oeko-Tex Standard 100.